



S.I.S. Security Intelligence

SIS-WT-2810-LI

DIGITAL GSM SPOT WIRETAP



The Digital GSM Spot Wiretap **SIS-WT-2810-LI** is a miniaturized GSM transmitter equipped with voice and vibration detector.

Designed for home, office and vehicles monitoring.

SIS-WT-2810-LI has a built-in Li-Ion battery that can work for a week without being re-charged.

Built-in Siemens® GSM Module. You can set 4 sensitivity voice levels of the microphone for detect voice in the area.

Auto dialing of Pre-defined Numbers (PN), or SMS alert, when voice and/or vibration is detected.

You can configure up to 3 Pre-defined Numbers where the **SIS-WT-2810-LI** would automatically call you when activated.

Custom functions settings can be remotely programmed by sending simple SMS commands.

Its tiny dimensions and the built-in rechargeable Li-Ion battery make it suitable to be concealed, carried anywhere and placed where it can not be detected.

Features:

- **VOICE ACTIVE MONITORING** – VAS (Voice Activation System) - when detect voice level higher then voice setting sensitivity, the **SIS-WT-2810-LI** module will send SMS and making call automatically.
- **SHOCK VIBRATION** – SAS (Shock Activation System) - The Digital GSM Spot Wiretap module can be activated automatically when it detects human voice, movements, vibrations or any kind of shock.
- **AUTOMATIC CALL** – When detect voices or vibrations the Digital GSM Spot Wiretap module will making call to Pre-defined Number automatically.
- **MICROPHONE SENSITIVITY** – You can set 4 sensitivity voice levels of the High-Quality microphone for detect voice in the target area.
- **SMS TEXT MESSAGE COMMANDS** – The Digital GSM Spot Wiretap module can be set through SMS text message commands for Shock Vibration, Microphone Sensitivity and Voice Detect functions.
- **BUILT-IN RECHARGABLE LI-ION BATTERY** – The Digital GSM Spot Wiretap module can work for a week without being re-charged (fully charged).

Technical Specifications:

- GSM Network: Tri-Band 900/1800/1900
- Siemens® GSM Module
- Password Protection SMS Text Message for Access Security
- Audio Sensitivity: -75db
- Microphone Sensitivity: 4 levels
- Pre-defined Numbers: 3 sets
- Built-in Li-Ion Battery: 3.7V DC - 900mAh
- Power Supply/Re-charger: 5V-6VDC 500mA
- Power Consumption: 20mA (stand by mode), 200mA (monitoring mode)
- Dimensions: 42 x 33 x 12 mm



Sicurezza - Electronic Intelligence - Investigazioni

Websites: <http://www.egisecurity.com> - <http://www.sisintsecurity.com>

Email: info@egisecurity.com - info@sisintsecurity.com

Via Garigliano 1/A - 03043 Cassino (FR) - Italy

Phone: +39 0776 319003 - 333 2136994

WEBFAX: +39 178 6037359

FAX: +39 0776 326415